


## Coaxial Cable Connector 25\_TNC-50-3-9/133\_N

### Description

Straight panel cable jack, flange mount

Interface standards

IEC 60169-17\_MIL-STD-348A/313\_CECC 22200



### Technical Data

#### Electrical Data

|                          |        |
|--------------------------|--------|
| Impedance                | 50 Ω   |
| Interface frequency max. | 11 GHz |

#### Mechanical Data

|                |           |
|----------------|-----------|
| Centre contact | soldered  |
| Outer contact  | clamped   |
| Weight         | 0.0181 kg |

#### Environmental Data

|                       |                  |
|-----------------------|------------------|
| Operating temperature | -65 °C to 165 °C |
| 2011/65/EU, RoHS      | compliant        |

#### Material Data

| Piece Parts    | Material               | Surface Plating                   |
|----------------|------------------------|-----------------------------------|
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Outer contact  | Brass                  | SUCOPLATE (R) Plating             |
| Body           | Brass                  | SUCOPLATE (R) Plating             |
| Insulator      | PFA / PTFE             |                                   |
| Gasket         | VMQ (Silicone rubber)  |                                   |

### Related Documents

|                      |                |
|----------------------|----------------|
| Outline drawing      | DOU-00009209   |
| Catalogue drawing    | DCA-00009210   |
| Assembly instruction | DOC-0000179064 |

### Ordering Information

|                |                      |
|----------------|----------------------|
| Single package | 25_TNC-50-3-9/133_NE |
|----------------|----------------------|

### Additional Information

|                 |   |
|-----------------|---|
| Suitable cables | RG_58_C/U, RG_223_/U, ENVIROFLEX_142, RG_400_/U |
|-----------------|---|