Data Sheet



Coaxial Panel Connector 13_716-50-0-4/003_-

Description

Straight panel receptacle plug, flange mount

Interface standards IEC 61169-4_CECC 22190_DIN 47223_VG 95250



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 50 \ \Omega \\ \text{Interface frequency max.} & 7.5 \ \text{GHz} \end{array}$

Mechanical Data

Number of matings 500
Weight 0.0981 kg

Environmental Data

Operating temperature -65 °C to 165 °C 2011/65/EU (RoHS) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Silver Plating
Outer contact	Brass	Silver Plating
Body	Brass	Silver Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Related Documents

Outline drawing DOU-00011259
Catalogue drawing DCA-00011261

Ordering Information

Bulk 20 pcs package 13_716-50-0-4/003_-V

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.