Data Sheet

HUBER+SUHNER Excellence in Connectivity Solutions

Coaxial Panel Connector 23_N-50-0-30/133_N

Description

Straight panel receptacle jack, flange mount

Interface standards
IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 50 \ \Omega \\ \text{Interface frequency max.} & 11 \ \text{GHz} \end{array}$

Mechanical Data

Number of matings 500
Weight 0.0146 kg

Environmental Data

Operating temperature -65 °C to 125 °C 2011/65/EU (RoHS) compliant

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|------------------------|-----------------------|
| Centre contact | Copper Beryllium Alloy | SUCOPRO Plating |
| Outer contact | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PFA / PTFE | |

Related Documents

Catalogue drawing DCA-00010110
Mounting hole DOU-00008784

Ordering Information

Single package 23_N-50-0-30/133_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.