Data Sheet

Coaxial Panel Connector 23_N-50-0-33/133_N

Description

Straight panel receptacle jack, flange mount

Interface standards IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data		
Impedance	50 Ω	
Interface frequency max.	11 GHz	
Mechanical Data		
Number of matings	500	
Weight	0.0248 kg	
Environmental Data		
Operating temperature	-65 °C to 125 °C	
2011/65/EU (RoHS)	compliant	
Material Data		
Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Related Documents		
Catalogue drawing	DCA-00010811	
Ordering Information		
Single package	23_N-50-0-33/133_NE	
0 1 0 .		

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER: 23_N-50-0-33/133_NE