Data Sheet

HUBER+SUHNER Excellence in Connectivity Solutions

Coaxial Panel Connector 23_TNC-50-0-2/133_N

Description

Straight panel receptacle jack, flange mount

Interface standards
IEC 60169-17_MIL-STD-348A/313_CECC 22200



Technical Data

Electrical Data

Impedance 50 Ω Interface frequency max. 11 GHz

Mechanical Data

Number of matings 500
Weight 0.0116 kg

Environmental Data

Operating temperature -65 °C to 165 °C 2011/65/EU (RoHS) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Related Documents

 Outline drawing
 DOU-00010312

 Catalogue drawing
 DCA-00010314

 Mounting hole
 DOU-00009051

Ordering Information

 Single package
 23_TNC-50-0-2/133_NE

 Bulk 100 pcs package
 23_TNC-50-0-2/133_NH

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.